
GM1700

☐ LM Series ☐ GM Series ☐ HM Series ☐ Speciality Equipment





This rotatry slope mower has a low center of gravity and pivoting seat which allows it to cut banks up to 25°.

GM1700 Features

- •The contour cutting deck improves the ability to follow undulating terrains.
- •The three-split unit trims the grass evenly on uneven and complex terrains.
- •The low center of gravity design improves operating performance and traction on slope areas.
- ·Optional SunShade and Protective net.

Specifications

Model			GM1700
Dimensions	Total length		100.39 in 255 cm
	Total width		60.63 in I 154 cm
	Total height	Roof	77.56 in I 197 cm
		steering wheel	47.64 in 121 cm
Weight (with ROPS and empty fuel tank)			1596.12 lb l 724 kg
Minimum turning radi	us		117.32 in I 298 cm
Engine		Model	Kubota D1105
		Туре	Vertical Water-cooled 4-cycle diesel engine
		Total displacement	68.52 cu.in. I 1,123 cm ³ (1.123 L)
		Maximum output	17.8 kW (24.2 PS)/2,800 rpm
Fuel tank capacity			Diesel 6.08 U.S.gal. Diesel 23.0 dm3 (23.0 L)
Operating width (Mowing width)			See the attachment's Operating Manual.
Operating height (Mowing height)			See the attachment's Operating Manual.
Blades			3
Drive			HST, 2WD/4WD selectable
		Forward	2WD: 0 - 9.94 mph l 0 - 16.0 km/h
Speed (HST)			4WD: 0 - 4.97 mph I 0 - 8.0 km/h
Sp354 (1.5.)		Reverse	2WD: 0 - 8.70 mph 0 - 14.0 km/h
			4WD: 0 - 4.35 mph 0 - 7.0 km/h
Efficiency			See the deck's specifications.
Maximum inclination for operation			25 degrees
Tire size		Front wheel	21 x 11.00 - 10
1110 0120		Rear wheel	21 x 11.00 - 10

The factory default maximum engine rpm is 2.800 rpm.

[AU/GB/US]





*The model shown is equipped with optional features.

Model		GM1700 contour deck
Widuei		GW1700 contour deck
Dimensions	Total length	42.52 in [100.39 in] I 108 cm [255 cm]
	Total width	72.05 in [72.05 in] I 183 cm [183 cm]
	Total height	14.57 in 37 cm
Weight		365.96 lb [1962.08 in] l 166 kg [890 kg]
Operating width (Mowing width)		59.45 in I 151 cm
Operating height (Mowing height)		1.38 - 3.74 mm 35 - 95 mm (0.59 mm spacing, 5 levels) (15 mm spacing, 5 levels)
Blades		3
Blade length		20.98 in 533 mm
Efficiency		1.5 acres/hour 6,040 m²/h (3.11 mph x mowing width x 0.8) (5.0 km/h x mowing width x 0.8)

*Values within [] are dimensions and weight of GM1700 equipped with the contour deck. [AU/GB/US]



Safety notes

Read the Owner's Operating Manual and other training material carefully. Be familiar with the controls, safety signs and the proper use of equipment before operation



Assurance inspection

 Regular inspection of the machine ensures long-lasting superior performance and safety. •There are parts of machine prone to wear and deterioration from long periods of use. Please consult with local dealer or distributor for proper inspection and maintenance schedule



株式会社 共栄社

KYOEISHA CO., LTD.

1-26, Miyuki-cho, Toyokawa-city, Aichi-pref, 442-8530 Japan TEL+81 533-84-1390 FAX+81 533-89-3623

www.baroness.co.jp



Your distributor or dealer

