

Specification



Model	SP05A (2WD)	SP05A (3WD)
Dimensions	Total length	84.65 in (with blade 90.55 in) 215 cm (with blade 230 cm)
	Total width	74.80 in 190 cm
	Total height	47.24 in 120 cm
Weight (with empty fuel tank)	974.43 lb 442 kg	1033.95 lb 469 kg
Minimum turning radius	133.46 in 339 cm	
Engine	Model	Vanguard 356447
	Type	Air-cooled 4-cycle gasoline engine
	Total displacement	34.78 cu.in. 570 cm ³ (0.57 L)
	Maximum output	13.2 kW (18.0 PS)/3,600 rpm
Fuel tank capacity	Gasoline 3.96 U.S.gal. Gasoline 15.0 dm ³ (15.0 L)	
Operating width (Mowing width)	109.06 in 277 cm	
Operating width (Mowing width)	Rake	74.80 in 190 cm
	Blade (option)	31.50 in (Weight: 55.11 lb) 80 cm (Weight: 25 kg)
	Cultivator (option)	45.67 in (Weight: 41.89 lb) 116 cm (Weight: 19 kg)
	Finishing brush (option)	76.77 in (Weight: 23.37 lb) 195 cm (Weight: 10.6 kg)
Drive	HST, 2WD/3WD selectable	
Speed (HST)	Forward	0 - 9.94 mph 0 - 16.0 km/h
	Reverse	0 - 3.73 mph 0 - 6.0 km/h
Maximum inclination for operation	15 degrees	
Tire size	Front wheel	PD21 x 11.00 - 10
	Rear wheel	25 x 13.00 - 9



*The model shown is equipped with optional features.

※ The factory default maximum engine rpm is 3,100 rpm.

[GB/US]

⚠ Safety notes

- Read the Owner's Operating Manual and other training material carefully. Be familiar with the controls, safety signs and the proper use of equipment before operation.

♥ Assurance inspection

- Regular inspection of the machine ensures long-lasting superior performance and safety.
- There are parts of machine prone to wear and deterioration from long periods of use. Please consult with local dealer or distributor for proper inspection and maintenance schedule.

株式会社 共栄社

KYOEISHA CO., LTD.

1-26, Miyuki-cho, Toyokawa-city, Aichi-pref, 442-8530 Japan

TEL+81 533-84-1390 FAX+81 533-84-1220

www.baroness.co.jp



Your distributor or dealer

BARONESS
Quality on Demand

Bunker Rake
SP05A



BARONESS is the global brand of Kyo-eisha Co., Ltd.

BARONESS
Quality on Demand

- Content and designs provided here are subject to change without notice.
- Colors in print may slightly vary from actual colors.
- Catalog No: SP05A-US/18A-0300-keywest

This Bunker Rake is designed to adapt to all kinds of bunker conditions with power steering, switchable 2WD/3WD, low center of gravity and free-floating adjustable rake and finishing brush.



Options



The Brush option beautifully finishes the bunker surface.



The front blade option smooths and evens the bunker.



The cultivator option breaks up and softens coarse sand.



< front >

The headlight options are mounted on the front and rear. These lights are useful for early morning operation.



< rear >



The cargo box option allows operator to carry cooler, walkie-talkie and other necessary tools.

SP05A Features

- Special rake design enables flexible rake movement.
- High-speed transport, can travel around course quickly.
- Power steering allows for shorter turning radius, also reducing operator fatigue.
- Low-vibration and low-noise.
- Front and rear covers open fully, for easy accessibility and maintenance.
- The foot brake increases safety.



Bunker Rake
SP05A